

12PM	1,812	0	12,144	19	11	
				23	12	!
1PM	2,050	0	14,325	23	12	:
1PM	2,050	0				1
						1
2PM	2,191	0	16,0 <b>96</b>	25	12	!
			·			
3PM	2,534	0	19.928	32	13	
4PM	2,859	180	21,983	35	14	1
			· · · · · · · · · · · · · · · · · · ·			
5PM	3,764	915	22,561	36	13	
6PM	2,839	185	21,046	33	13	
7PM	2,902	71	20,610	33	12	:
8PM	5,621	3,019 .	22,641	36	15	
				36		
9PM	8,210	5,909	22,701	36	16	
10PM	7,251	4,931	22,714	36	16	\$9.95/mo 1st 5 hrs
11PM	3,807	1,662	22,076	35	17	(each addit hr \$2.95
Total	54,704	16,908	327,303	22	14	





#### HOLD TIME (min)



HOLD TIME

	Hempstead DMS-10	00 DS0 Line MLHG	Data for TI (28 8/14 4/		ruary 8, 1996	
HOURS	CALL ATTEMPTS	OVERFLOW	USAGE	CCS/LINE	HOLD TIME	(min)
12AM	564	539	786	36	52	
1AM	89	63	716	33	46	
2AM	8 .	0	454	21	95	
3AM	- · · · · · · <del> · · · · · · · · ·</del>	0	229	10	55	
4AM	3	0	166	8	92	
5AM	5	0	103	5	34	
6AM	7	0	179	<u>8</u>	43	
7AM	27	<del></del>	363	17	22	
8AM	24	0	386	18	27	
9AM	25		388	18	<u>26</u>	
10AM	22	0	497	23	38	
11AM	112	73	618	28	45	
12PM	158	120	749	34	33	· · · · · · · · · · · · · · · · · · ·
12PM 1PM	102	74	724	33	43	
			643	29	26	
2PM 3PM	59 87	50	712	32	32	****
4PM	179	153	784	36	50	
5PM	461	432	789	36	45	
6PM	254	230	781	36	54	
7PM	896	865	789	36	42	
8PM	714	682	790	36	41	
9PM	471	442	784	36	45	\$9.95/mo 1st 5 hrs
10PM	508	472	788	36	36	(each addit hr \$2.50)
11PM	573	549	791	36	55	\$19.95/mo unlimited hi
Total	5,355	4,762	14,009	27	39	
40			CCS/LINE			
35						
25						
·5		<del></del>			<del></del>	
10						
5						
12AM	CAM 4AM 5AM	3AM 10AM	12PM 25	PM 4PM	6P <b>M</b> 8P <b>M</b>	10P <b>M</b>
			HOLD TIME (	min)		
	<b>↑</b>					
3C	/. \ / \					ł
ļ						HOLD TIN

	West St DMS-100 D			onday April :	22, 1996	
	<del></del>	Line MLHG				
HOURS	CALL ATTEMPTS	OVERFLOW				(min)
12AM	376	3	5,100	27	23	
1AM	302	0	4,973	26	27	
2AM	58	0	2,211	12	64	and the second discount of the second and second
3AM	26	0	1,270	7	81	
4AM	25	0	754	4	50	
5AM	35	0	251	1	12	
6AM	40	0	847	4	35	
7AM	81	0	1,181	6	24	
ВАМ	147	0	1,985	10	23	
9AM	260	0	2,910	15	19	
10AM	330	0	4,247	22	21	<del></del>
11AM	233	0	3,789	20	27	
12PM	295	0	4.091	21	23	· · · · · · · · · · · · · · · · · · ·
1PM	278	0	3,930	21	24	
2PM	303	0	4,320	23	24	
3PM	315	0	4,436	23	23	
4PM	393	<u>0</u>	4,586	24	19	
5PM 6PM	318 360		4,771 4,337	25 23	25 20	
7PM	348		4,337	23	20	
8PM	408	0	4,230	<u>22</u>	18	
9PM	420		4,530	24	18	\$9.95/mo 1st 5 hrs
10 <b>PM</b>	511	0	5,174	27	17	(each addit hr \$2.50)
11PM	510	36	5.203	27	18	\$19.95/mo unlimited hr
Total	6,372	39	83,627	19	22	TO TO SOME OF THE OTHER
TOTAL	0,312		03,027	13	44	
			CCSALINE			
30						<b>—</b>
25			اسهدهم			
:5	<del>_</del>	<b>/</b>	<del></del> -			CCSAINE
10	. • • • • • • • • • • • • • • • • • • •					
5				<del></del>		
12AM	CAM 4AM 6AM	BAM 10AM	129 <b>M</b> 28	PM 4PM	RPM BPM	10PM
			HOLD TIM	Ε		
						<del></del> -
30					<b></b>	
30						
30 50						
80 50 50						→ HOLD TIMI
30 50						HOLD TIMI
80 70 50 50 40						—— HOLD TIME

The state of the s

	GRCYNYGCDS0 5			Monday Febru	ary 19, 1996	
	201	Line MLHG	(14.4)			
OURS	CALL ATTEMPTS	OVERFLOW	USAGE	CCS/LINE	HOLD TIME	
12AM	228	0	4.920	24	36	
1AM	93	0	3.520	18	63	
2AM	53	0	2,047	10	64	
3AM	36	0	1,618	8	75	
4AM	19	0	1,103	5	97	
5AM	15	00	663	3	74	
6AM	30	0	571	3	32	
7AM	85	0	697	3	14	
8AM	133	0	1,430	7	18	
9AM	177	0	1,636	8	15	
10AM	304	0	2,713	13	15	
11AM	309	0	3,621	18	20	
12PM	353	0	3,457	17	16	
1PM	272	0	3,402	17	21	
2PM	337	0	3,886	19	19	
3PM	291	00	4,370	22	25	
4PM	293	0	4,129	21	23	
5PM	357	0	4,587	23	21	**************************************
6P <b>M</b>	341	00	4,266	21	21	\$9.95/mo 1st 5 hrs
7 <b>PM</b>	361	0	4,002	20	18	(each addit hr \$2.95)
8PM	386	0	4,880	24	21	\$14.99/mo 1st 15 hrs
9 <b>PM</b>	481	0	5,335	27	18	(each addit hr \$2.95)
10PM	530	0	6,137	31	19	\$29.99/mo 1st 30 hrs
11PM	337	00	5,606	28	28	(each addit hr \$2.95)
Total	5,821	0	78,596	16	23	
			CCS/LINE			
35						
35 🙀						
00 <b></b> -			ستنت	A-2-4-1	*****	
5						
5		كاستعر				]
٥ ــــــــــــــــــــــــــــــــــــ			<del></del>			
12AM	2AM 4AM 6AM	3AM 10AM	12P <b>M</b> 2	2 <b>PM</b> 4PM	6PM 8PM	10PM
			HOLD TIME	(min)		
100						
80		~				
50 🏂						
40						
20						

.....

			HOLD TIME (m	un)		
5 CAM	ZAM 4AM 5AM	BAM 10AM	12PM 2PM	4 4PM - 6		10PM
20						
30 ,						<b>₹</b>
			CCSAINE			
Total	3,535	0	41,641	14	20	(
11PM	206	0	3,132	24	25	(each addit hr \$2.95)
10PM	240	0	3,524	28	24	\$29.99/mo 1st 30 hrs
8PM 9PM	264 247	0	2,771 3,382	22	17 23	\$14.99/mo 1st 15 hrs (each addit hr \$2.95)
7PM	214	0	2,132	17	17	(each addit hr \$2.95)
6PM	172		1,983	15	19	\$9.95/mo 1st 5 hrs
5PM	269	0	2,534	20	16	
4PM	250	0	2,427	19	16	
3PM	200	0	2,105	16	18	
2PM	182	0	1,995	16	18	
1PM	191	00	2,345	18	20	
12PM	212	0	2,013	16	16	
11AM	204	0	1,085	8	9	
10AM	195	0	1,631	13	14	
9AM	126	0	1,023	8	14	
8AM	93	0	758	6	14	
7AM	53	<u>_</u>	465	· · <del>-</del> - ·	15	
6AM	20		269	<u>2</u>	22	
5AM	8	0	264	2	55	
4AM	<u> </u>		364	3	103	
2AM 3AM	. <u>28</u> . 8		944 492		56	
1AM	45	0	1,521	12 7	56	
12AM	102	0	2.482	19	. 41	
IOURS	CALL ATTEMPTS				HOLD TIME	(min)

12AM

CAM

4AM

MAĉ

8AM

10AM

:2**PM** 

2**PM** 

4PM

5**PM** 

8**PM** 

10PM

# ATTACHMENT E

### **Technological Alternatives**

Bell Atlantic and NYNEX are investigating various alternatives in an attempt to alleviate congestion problems on their networks. These alternatives are segregated into two categories: Overlay Network Architecture solutions and Data Off Load solutions. These solutions are designed to be used in connection with packet data networks such as Bell Atlantic's Internet Protocol Routing Service (IPRS) and NYNEX's Information Protocol Access Service (IPAS).

IPRS and IPAS provide for the collection, concentration and management of the ISPs' traffic within a LATA using the Transmission Control Protocol/Internet Protocol (TCP/IP) standard. These services consist of network routers (located at LATA hub sites) which collect dial-up or dedicated access data traffic, concentrate the traffic, and route it via packet data services between the ISP customer's network and its end users. Currently Switched Multimegabit Data Service ("SMDS") is the transport mechanism for IPRS, while IPAS will use Frame Relay ("FR") service for transport. ISPs purchase ports that provide 23 call paths and can be configured for analog, ISDN, DDS, DS1 or frame relay (56 kbps or 1.544 Mbps) IPRS does not include connections to the end user access service, which are provided through the existing circuit-switched public telephone network.

In addition to providing more efficient transport of Internet calls, IPRS and IPAS help to reduce the adverse impact on the circuit-switched network by alleviating congestion at the central offices that serve ISPs. They do not bypass the end user's originating central office switch, however, so they will not relieve congestion at that location.

IPRS became available in April 1996 (Bell Atlantic Tariff F.C.C. No. 1. Section 16). IPAS will be available later this year.

The following solutions are all under study. Neither Bell Atlantic nor NYNEX has determined whether any will be cost-effective, and neither company has committed to deploying them.

#### 1. OVERLAY NETWORK ARCHITECTURE SOLUTIONS

The following alternatives use a separate network for transporting Internet traffic:

#### Data Interceptor Plans

These involve the use of data intercept equipment to remove a significant portion of Internet traffic from the public switched network at the line side of the end user's serving switch. Specifically, these proposals include 1) deploying data interceptor equipment in front of the end user's serving switches to divert the heaviest Internet traffic volumes from the switch; 2) deploying equipment to concentrate Internet traffic from the data interceptors and the serving switch; 3) adding router equipment to existing hubs, and creating new hub routers to permit packet data handoff to ISPs if required; 4) augmenting the packet-switched data network where required; and 5) in some cases utilizing SS7 Queries to route Internet users to dedicated

equipment. This alternative will reduce congestion in originating and terminating switches and on inter-office networks, but its success depends upon all ISPs providing Bell Atlantic and NYNEX with up-to-date lists of their access telephone numbers.

#### Trunk Side Redirect to Overlay Network

This alternative involves redirecting Internet traffic to a dedicated network after the traffic is switched through the serving switch, but minimizing the impact on other users of that switch, by 1) adding special line side equipment to the serving switch designed to eliminate call blocking; 2) augmenting the PSTN for ISDN traffic; 3) deploying equipment designed to concentrate Internet traffic from the data interceptors and the serving switch; 4) adding router equipment to existing hubs, and creating new hub routers to permit packet data handoff to ISPs if required; and 5) augmenting the packet-switched data network where required. Disadvantages are that 1) this alternative does not eliminate congestion on the line side of the customer's serving central office switch; 2) it requires a substantial investment; and 3) significant labor costs will be incurred to transfer lines from existing to new equipment.

#### 2. DATA OFF LOAD SOLUTIONS

The following alternatives could be used to divert a portion of Internet traffic off of the existing or overlay networks:

#### x Digital Subscriber Line (xDSL) Solution

This alternative would use the proposed ISDN Digital Subscriber Line and Asymmetrical Digital Subscriber Line services. Initial analysis shows that this alternative will remove some traffic from the serving switch and the existing or overlay network. However, xDSL technology can currently be used in a limited number of locations, because it is compatible with only certain types of existing copper cable plant.

#### Switched Broadband Network (SBN) Solution

This alternative involves transporting Internet data over a separate Switched Broadband Network. The advantages are: 1) it provides a totally integrated line: 2) it allows for high bandwidth; and 3) it has a high level of flexibility for future applications. The disadvantages include: 1) delay, because high speed data capability over the SBN will not be available until late 1998 at the earliest; 2) many unknowns, such as ease of deployment, network recovery, reliability, interoperability, need to be addressed before this technology can be used; 3) the cost and availability of customer premises equipment have not yet been addressed; 4) standards for this technology are not complete; 5) network monitoring systems have not been developed; and 6) the cost may be much higher than other solutions.

## CERTIFICATE OF SERVICE

I hereby certify that on this 24th day of March, 1997 a copy of the foregoing "Joint Comments of Bell Atlantic and NYNEX on Notice of Inquiry" was served by hand on the parties on the attached list.

Tracey M. De Vaux

Mr. William F. Caton Office of the Secretary Federal Communications Commission 1919 M Street, NW Room 222 Washington, DC 20554

(16 paper copies and 1 diskette copy)

ITS, Inc. 1919 M Street, NW Room 246 Washington, DC 20554 Competitive Pricing Division Common Carrier Bureau Federal Communications Commission 1919 M Street, NW Room 518 Washington, DC 20554

(2 copies)